

G5-YG Yellow & Green striped polyolefin tubing

Applications

The unique yellow-green striped color tubing is used for the ground wire identifying. It is widely used in the fields of wire marking, color coding as well as electrical insulation.

Operating temperature range

Operating temperature: -55°C~125°C

Minimum shrink temperature: 70°C

Full recovery temperature: Above 110°C



UL file No. E255532

Product Dimensions

Part Number	Size(mm)		As supplied (mm)		After recovered (mm)		Standard Length (Meter)
	mm	Inch	I.D.	W.T.	I.D.(max)	W.T.(min)	
G5-YG0016	1.6	1/16	2.0±0.3	0.20±0.05	0.75	0.36	200
G5-YG0024	2.4	3/32	3.0±0.3	0.25±0.05	1.25	0.44	200
G5-YG0032	3.2	1/8	3.5±0.3	0.25±0.05	1.50	0.44	200
G5-YG0048	4.8	3/16	5.0±0.3	0.25±0.05	2.25	0.44	100
G5-YG0064	6.4	1/4	6.5±0.3	0.28±0.05	3.0	0.56	100
G5-YG0080	8.0	5/16	8.6±0.3	0.30±0.07	4.0	0.56	100
G5-YG0095	9.5	3/8	9.6±0.3	0.30±0.07	4.5	0.56	100
G5-YG0127	12.7	1/2	12.7±0.4	0.30±0.07	6.0	0.56	100
G5-YG0160	16.0	5/8	16.7±0.5	0.35±0.08	8.0	0.69	100
G5-YG0191	19.1	3/4	19.0±0.5	0.40±0.10	9.0	0.77	100
G5-YG0254	25.4	1	26.0±1.0	0.45±0.10	12.5	0.87	50
G5-YG0318	31.8	1 1/4	31.5±1.0	0.45±0.10	15.0	0.87	50
G5-YG0381	38.1	1 1/2	41.5±1.0	0.50±0.10	20.0	0.97	50
G5-YG0508	50.8	2	51.5±1.0	0.55±0.10	25.0	0.97	25