



## AEC Heat shrinkable cable end cap

### Applications

It is injection-molded with polyolefin and has UV and abrasion resistance. Hot melt adhesive is coated in a spiral shape inside the tube, providing reliable waterproof and insulation protection for the cut surface of cables or air-filled cables.

### Operating temperature range

Operating temperature: -55°C~110°C

Minimum shrink temperature: 80°C

Full recovery temperature: Above 120°C

### Product Dimensions

Part Number	As supplied (mm)		After recovered (mm)			Cable diameter (mm)
	H (min)	L (±10%)	H (max)	A (min)	W (±10%)	
Standard Length						
AEC012	12	38	4.0	12	2.6	4-10
AEC014	14	45	5.0	15	2.2	5-12
AEC020	20	65	6.0	19	2.5	6-16
AEC025	25	75	8.5	23	2.5	10-20
AEC035	35	92	16.0	25	3.3	17-30
AEC040	40	95	15.0	25	3.3	18-32
AEC055	55	114	26.0	36	3.5	28-48
AEC075	75	132	36.0	40	4.2	45-68
AEC100	100	153	52.0	55	5.0	55-90
AEC120	120	155	60.0	55	5.0	65-110
AEC145	145	160	60.0	55	5.0	70-130
AEC160	160	160	82.0	55	4.5	90-150
AEC200	200	170	90.0	55	4.5	100-180